Note: This datasheet may be out of date

Please download the latest datasheet of XRCGB24M000F3M13R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=XRCGB24M000F3M13R0

XRCGB24M000F3M13R0










Appearance & Shape







Features

The crystal unit that realized small package and highly accurate frequency.

Based on Murata's excellent package technology and high grade quartz crystal elements, achieving small size and high accuracy resonators.

Features

- 1. The series is available in the applications to be necessary for high accuracy resonator. Especially, it is the best for the communication clocks such as S-ATA and USB2.0.
- 2. The resonator is extremerly small size (2.0 x 1.6 x 0.7 (mm)), and contribute to reduction in mounting area.
- 3. The series complies to RoHS directive, being lead-free (phase 3).



Other Usage

Consumer



Packaging Information

Packaging	Specifications	Minimum Order Quantity
R0	180mm Plastic Tape	3000

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: http://www.murata.com/

Last updated : 2017/09/08

Note: This datasheet may be out of date. $\underline{ Please \ download \ the \ latest \ data sheet \ of \ XRCGB24M000F3M13R0 \ from \ the \ official \ website \ of \ Murata}$ Manufacturing Co., Ltd. http://www.murata.com/en-us/products/productdetail?partno=XRCGB24M000F3M13R0

XRCGB24M000F3M13R0



Туре	HCR2016	
Frequency	24.0000MHz	
Frequency Tolerance	±30ppm max. (25±3°C)	
Operating Temperature Range	-30℃ to 85℃	
Frequency Shift by Temperature	±40ppm max.	
Frequency Aging	±5ppm max./year	
Wash	Not available	
Load Capacitance	8.5pF	
Equivalent Series Resistance(max.)	120Ω	
Drive Level(max.)	300µW	
Shape	SMD	
L x W (size)	2.0x1.6mm	

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.


Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: http://www.murata.com/

XRCGB24M000F3M13R0





Temperature Characteristics

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: http://www.murata.com/